

# 120cm Alfresco Canopy RANGEHOOD

PRODUCT CODE: **AA.000.000.001.001.005**



## FEATURES:

- + 304 Grade stainless steel
- + 3 speed motor
- + 2000m<sup>3</sup> / hr extraction capacity
- + 4x 1.5W LED lights
- + Remote control
- + 8x stainless steel baffle filters
- + Electronic control with LCD display
- + 1200mm x 800mm coverage
- + 2x 150mm Flue diameter

## HIGH EXTRACTION CAPACITY

The extraction capacity of 2000m<sup>3</sup>/hr provides strength and power to this stylish range hood.

## COMMERCIAL STYLE BAFFLE FILTERS

Easy clean, stainless steel baffle filters, are designed to capture all steam & moisture, whilst removing exhaust & odors.

## 3 SPEED MOTOR

This rangehood provides the option of 3 different speed levels ensuring you have the option to use your rangehood at a low, medium or high level of operation.

## LOW NOISE LEVELS

The motor in the ERB120SS3R has been designed to provide maximum extraction with minimum noise.

## SPECIFICATIONS:

<b>Electrical Requirements</b>	Rangehood is supplied with 10amp cord & plug.
<b>Decibel Rating</b>	52-60-65 dBA
<b>Available Ventilation Kits</b>	2 vent kits are required for this canopy RHKE65EU Wall – Eave vent kit RHKMR65EU Universal metal roof kit (includes flashing) RHKTR65EU Universal tile roof kit (includes flashing)
<b>Recirculating Options</b>	This rangehood cannot be recirculated
<b>Product Dimensions</b>	W1200mm x D800mm
<b>Barcode</b>	<b>9347726028415</b>

# MODULR<sup>+</sup>

www.modulr.com.au



**Warranty**

## HELPFUL TIPS

- + Leave your range hood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
- + The baffle filters need to be cleaned after approximately 1 month of standard operation
- + It is also recommended that fumes from the rangehood be ducted out into the atmosphere.
- + Turn off the range hood before attempting to clean

## INSTALLATION INFORMATION

Warning: This canopy is not an outdoor appliance, but it can be installed in an alfresco area in accordance with the following:

- + Installation must be performed by a qualified competent installer.
- + The canopy cannot be exposed to rain, moisture or dust.
- + Do not install in a location where winds may blow water or dust onto the canopy.
- + If installed above a barbecue, the minimum distance from the cooking surface is 1200mm
- + If installed above a cooking appliance, the minimum distance from the cooking surface is 650mm.

